

EZ-V(R)

Imperial	95160	95150
Blade Width	7'6"	7'6"
Moldboard Options	Stainless Steel (SS)	Powder-Coated Steel (PC)
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
Approx. Weight* (Without Mount)	550 lbs	510 lbs
Plowing Width	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"
Blade Height	At Center: 27" At End: 33"	At Center: 27" At End: 33"
Blade Thickness	14 ga	14 ga
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	1¼" x 8.63"	1¼" x 8.63"
Angling Rams	1½" x 12"	1½" x 12"
Cutting Edge	3/8" x 6" (Standard)	3/8" x 6" (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

Metric	95160	95150
Models	95160	95150
Blade Width	2.29 m	2.29 m
Moldboard Options	Stainless Steel (SS)	Powder-Coated Steel (PC)
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
Approx. Weight* (Without Mount)	249 kg	231 kg
Plowing Width	Full Angle: 2.01 m Scoop: 1.96 m Full V: 2.06 m	Full Angle: 2.01 m Scoop: 1.96 m Full V: 2.06 m
Blade Height	At Center: 68.58 cm At End: 83.82 cm	At Center: 68.58 cm At End: 83.82 cm
Blade Thickness	14 ga	14 ga
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	3.18 cm x 21.91 cm	3.18 cm x 21.91 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Cutting Edge	230.43 kg (Standard)	230.43 kg (Standard)
Mount Type	Minute Mount® 2	Minute Mount® 2

* Does not include vehicle mount (approx. 60 lbs for v-plows). Please refer to the eMatch program for specific vehicle applications.